




SCALE 1:60




KENGURU PRO

"KENGURU PRO" LTD

Address: Lauteres street 4, Riga, Latvia, LV-1002
 VAT Reg. No. 40103750152
 Bank: A/S Luminor bank, SWIFT: RIKOLV2X,
 Bank Account: LV65RIKO0002930161161
 e-mail: info@kengurupro.eu
 www.kengurupro.eu

PK-009

Kenguru PARKOUR



The structure consists of twelve vertical columns, two wooden wall sections of different heights, one crossbar 1200 mm in length and ten crossbars 1758 mm in length. The wall is mounted on two crossbars 1200 mm in length. Heights of the walls are 1050 mm and 1650 mm. The structure is secured together with siluminium clamps at the height that corresponds to the wishes of the Client. Weight – 676,30 kg

Installation instructions:

- Choose a suitable underground for the unit (see page 2, table 2)!
- Prepare the construction pit with a drilling machine or other devices.
- Before pouring the concrete all structures elements must be leveled and fixed.
- Complex elements must be fixed and bolted together with metal clamps.
- Ready-made C25 concrete should be used.
- Crossbars installation height can be changed according to customer's wishes.
- Approximately 0,15m³ concrete is needed for each spot foundation.
- Under the structures we recommend to install absorbing rubber cover.

The size of the hole for the foundation is depending on the consistency of the ground. The dimensions mentioned above are applicable for normal conditions with firm ground. If the ground is extremely soft, a much bigger foundation is needed. Use only appropriate material and follow the installation instructions closely!!!

Foundation plan and area of movement of the Kenguru PARKOUR complex PK-009				Technical information	
Foundation when using Shock absorbing underground (synthetic - rubber granulates)		Beveling of foundation when using loose filling material		width:	5148 mm
				height:	2650 mm
				length:	5148 mm
				largest part:	2650 mm
				weight:	676,3 kg
				floor space required 9298 x 9348 mm	
				pipe measurements: diameter: wall thickness:	
				108 mm 3.2 mm	
				33.7 mm 3.2 mm	
				metal parts:	steel, galvanized, powder coated RAL 7016 (anthracite grey)
				metal clamps:	siluminium, powder coated, RAL 5018 (turquoise blue)
				bolts for metal clamps:	stainless steel, Pin Hex Button Head Security bolts M10
				wooden beam measurements:	Height, width Length
				75 x 100 mm 1650 mm	
				wooden parts:	Accoya, Tikkurila Terrace oil coated
				max. free fall height:	< 2450 mm possible underground see DIN 79000:2012-05 Tab.2 or installation instructions
				user height:	> 140 cm
				maximum user weight:	130 kg
				certificates:	TÜV Rheinland InterCert Kft.

